



Batch Mixers

Capacity

4 – 30,000 litres.

Workheads

Interchangeable workheads available for all models.

Materials of Construction

Product contact parts in 316L stainless steel. Non-standard materials such as mild steel or Hastelloy available on request.

Motor Specification

1-200 kW, TEFV, flame proof, ATEX approved and stainless steel motors available as standard.

Mounting

All mixers can be supplied with either a rectangular or circular flange for mounting on the vessel. Smaller models can be mounted on specially constructed mobile hydraulic floor stands.

Sealing

Where sealing is required, lip seals and single or double mechanical shaft seals can be supplied.

Cleaning

Simple, easy-to-clean construction.

Batch Mixers, 50Hz Motors - Metric Dimensions

	kW	R.P.M.	A	B	TEFV		EExD		D	E	F	G	H	I	J	K	CAPACITY (litres)	
					C	C	Water Visc.	High Visc.										
BX	0.75	3000	118	610	277	312	229	229	178	203	4x10	254	203	6x10	220	20		
DX	1.5	3000	160	690	303	330	254	254	203	229	4x10	254	203	6x10	450	50		
EX	3	3000	165	790	334	379	305	305	267	267	4x11	337	292	6x11	675	90		
FX	4	3000	165	1042	334	379	305	305	267	267	4x11	337	292	6x11	1200	150		
GX10	7.5	3000	286	1220	413	460	305	407	254	369	4x11	407	356	6x11	1800	275		
GX10	7.5	1500	286	1220	413	460	305	407	254	369	4x11	407	356	6x11	2250	400		
GX20	15	3000	286	1220	561	600	381	483	305	432	4x14	407	356	6x14	2250	400		
700X	11	1500	368	1525	561	600	482	381	432	305	4x14	483	406	6x14	3500	*		
HX10	7.5	1000	419	+	565	605	520	432	476	381	4x17.5	584	521	6x20.5	5000	*		
HX30	22	1500	419	+	670	710	520	432	476	381	4x17.5	584	521	6x20.5	5000	*		
JX	15	1000	419	+	670	710	520	432	476	381	4x17.5	584	521	6x20.5	7000	*		
KX	from 30	1000	610	+	860	935	864	711	787	610	4x17.5	864	794	8x17.5	10000	*		

+ Length adjusted to suit vessel.
* Capacities available on request.

