

Zhucheng Yuanyang Imp & Exp Co.,Ltd

Add: Shunwang Industry Park,Zhucheng City, Shandong Province,China

Zip Code: 262200

Technical Parameter

Item Content	Technical Parameter	
Model	NH-2000	
Full volume	2000L	
Working capacity	1400L	
Material	Inner shell	SUS304 polished & 12 mm steel plate thickness
	Jacket	Carbon steel Q235 coated with antirust paint & 8 mm steel plate thickness
	Sigma Blade	SUS304 polished
		Sigma blade designed to be hollow for cooling / heating
Motor	55KW (Siemens)	
	Equipped with Gear reducer	
	Equipped with Frequency Inverter (Siemens)	
Rotation speed	Fast blade: 0-33 RPM adjustable	
	Slow blade: 0-23 RPM adjustable	
Heating method	Thermal oil heating	
Discharge	Screw extrusion	
	Extrusion motor: 22 KW (Siemens)	
	Extrusion motor equipped with Frequency Inverter (Siemens)	
	Screw extruder diameter: 165 mm	
	Extrusion speed : adjustable	
Vacuum system	Vacuum pump : 15 KW	

Zhucheng Yuanyang Imp & Exp Co.,Ltd

Add: Shunwang Industry Park,Zhucheng City, Shandong Province,China

Zip Code: 262200

	Buffer tank ,Pressure gage and vacuum pipe equipped
Cover opening	Hydraulic opening
	Hydraulic pump motor: 1.5 KW (Siemens)
Seal method	Packing Seal PTFE
Rotation Speed	Fast speed : adjustable
	Low speed :adjustable
Design on the Cover	1) Powder feeding hole flange (1 piece)
	2) Sight glass flange (2 pcs)
	3) Vacuum hole flange (1 piece)
	4) Air Exhaust Hole Flange: (1 piece)
Control panel	1 set
Power supply	380V,50Hz,3 Phase